




- Rugged construction
- Quick fit quick installation
- Moulded coaxial cable


The performance and range of portable equipment can often be considerably improved by better positioning of the antenna. Spring clip antennas provide an easy way to do this, providing elevation and clearance from surrounding objects. The combination of better positioning with the performance of an end fed 1/2 wave antenna makes the CD range ideal for temporary and semi permanent applications.

The jaws of the spring clip are moulded in nylon and are fully adjustable for any angle. The antenna is protected from the elements by a weather protective moulding around the coaxial feeder cable.


Typical H-Plane (420MHz)



Typical E-Plane (420MHz)




Typical VSWR*



*Measured in free space with 3m (9.8') CS23 cable

Technical Drawing



Part No.

CD420

Electrical Data

| | |
|-----------------------|------------------|
| Frequency Range (MHz) | 410-430 |
| Operational Band | S2 |
| Peak Gain: Isotropic | 3dBi |
| Compared to ¼ wave | 1dB |
| Typical VSWR | ≤ 1.5:1 |
| Polarisation | Vertical |
| Pattern | Omni-directional |
| Impedance | 50Ω |
| Max Input Power (W) | 5 |

Mechanical Data

| | |
|---------------------|-------------------------------|
| Total length (mm) | 355 (14") |
| Operating Temp (°C) | -40° / +80°C (-40° / 176°F) |
| Colour | Black |

Cable Data

| | |
|---------------|----------|
| Type | CS23 |
| Length (m) | 3 (9.8') |
| Diameter (mm) | 5 (0.2") |

PANORAMA ANTENNAS

Panorama Antennas Ltd
Frogmore, London, SW18 1HF, United Kingdom

T: +44 (0)20 8877 4444
F: +44 (0)20 8877 4477
E: sales@panorama-antennas.com
www.panorama-antennas.com

Waiver: The data given above is indicative of the performance of the product/s under particular conditions and does not imply a guarantee of performance. These specifications are subject to change without notice.

Copyright © Panorama Antennas Ltd. All rights reserved.